

---

# Ace Lamps

A division of Direct Electrical Services

---

[Click here to view website](#)

## INSTALLATION GUIDE FOR 392-1CH, 392-2CH BATHROOM WALL LIGHTS



[View 392-1CH Bathroom light](#)



[View 392-2CH Bathroom light](#)

**IMPORTANT: PLEASE READ BEFORE COMMENCING INSTALLATION.**

**WARNING:**

- It is recommended that this luminaire be installed by a qualified electrician in accordance with current IEE Wiring Regulations and UK Building Regulations.

- Ensure that the mains electrical supply is isolated before commencing any installation.
- This luminaire must be earthed.

1. Expose mains supply Live, Neutral and Earth wires.
2. Remove shade collar and decorative plate if fitted. Remove set screws and prise front cover away from back plate.
3. Mark the position of the fixing holes in the back plate, on the wall avoiding any wiring run in the wall.  
Drill and prepare the holes for the screws ensuring that the fixings are into a solid material.  
If wall luminaire have to be fastened onto plasterboard or hollow walls ensure suitable fixing bolts are used. Do not use screws directly into the plasterboard.
4. Pass incoming mains cable through rubber grommet in back plate.
5. Ensure that at the luminaire will be adequately supported, without any strain being placed on the wiring.
6. Connect the supply cables to the wires of the luminaire by means of connector blocks as follows:

Incoming Live (brown or red) to luminaire live (brown) wire (or terminal marked 'L')

Incoming Neutral (blue or black) to luminaire neutral (blue) wire or terminal marked 'N'

Incoming Earth (green or green/yellow) to luminaire earth (green/yellow) wire or earth terminal.

7. Ensure that all connections are adequately tightened and that no strands of bare wire have escaped the terminals.
8. Replace the front cover onto the back plate and secure with set screws.
9. Secure the luminaire to the wall using the wall fixing screws. Take care not to damage or trap any of the wires or leave any wires exposed.
10. Re-fit decorative cover plate ensuring thin silicone washers are in place.
11. Fit the lamp bulb of type indicated on the luminaire. Do not exceed stated maximum wattage.
12. Re-fit collar and thick silicone washer and screw glass shade onto lamp holder.
13. Switch on the supply to the luminaire and ensure it operates correctly.

**Fittings should not be mounted on normally combustible surfaces unless marked with symbol F.**

**F with a cross through indicates that the fitting is not suitable for fitting to normally combustible surfaces.**

Do not install on freshly plastered, painted or wallpapered surfaces that have not had reasonable time to dry out. This is to avoid the possibility of discoloration occurring at the edge of the plate.

Clean only with a dry or damp cloth. Do not use polishes or cleaners.

[Click to view our range of bathroom lighting](#)