

---

# Ace Lamps

A division of Direct Electrical Services

---

[Click here to view our website](#)

INSTALLATION GUIDE FOR [1303/5GO](#) , [1303/5CH](#), [1303/3GO](#), [1303/3CH](#) LIGHT FITTINGS



[View Product](#)



[View product](#)

**IMPORTANT PLEASE READ BEFORE COMMENCING INSTALLATION.**

**WARNING:**

- It is recommended that this luminaire be installed by a qualified electrician in accordance with current IEE wiring regulations & UK Building Regulations.
- Ensure that the mains electrical supply is isolated before commencing any installation.
- This luminaire is Double Insulated and does not require earth.

1. Remove mounting bracket.
2. Mark the position of the fixing holes in the mounting bracket on the wall, avoiding any wiring run in the wall.  
Drill and prepare the holes for the screws ensuring that the fixings are into a solid Material. If wall luminaries have to be fastened onto plasterboard or hollow wall Ensure suitable fixing bolts are used. Do not use screws directly into the plasterboard.
3. Partially insert side screws into mounting bracket.
4. Remove plastic cover plate inside luminaire.

5. Thread mains supply cable through hole in cover plate and connect to the luminaire as follows:

Incoming live (brown or red) to connector block terminal adjacent to luminaire brown Wire.

Incoming neutral (blue or black) to connector block terminal adjacent to luminaire blue wire.

Ensure that all connections are adequately tightened,.

6. Ensure that no strands of bare wire have escaped the terminals, and replace plastic cover plate.
7. Secure the luminaire to the mounting bracket by placing slots over screw heads in mounting bracket, and twisting to lock in position. Tighten the side screws. Take care not to damage or trap any of the wires or leave any wires exposed.
8. Fit the lamp bulb/s of type indicated on the luminaire.
9. Gently push on glass shades.
10. Switch on the supply to the luminaire and ensure it operates correctly.

#### 11. Replacement Lamps

This luminaire should only be fitted with 40 watt G9 lamps.

#### **ALWAYS SWITCH OFF MAINS SUPPLY BEFORE CHANGING LAMPS**

Allow lamps to cool down before changing.

Fittings should not be mounted on normally combustible surfaces unless marked with symbol "F"

F with a cross through indicates that the fitting is not suitable for fitting to normally combustible surfaces.

Do not install on freshly plastered, painted or wallpapered surfaces that have not had reasonable time to dry out. This is to avoid the possibility of discolouration occurring at the edge of the plate.

Clean only with a dry or damp cloth. Do not use polishes or cleaners.

[Click here to View our full range of lighting products](#)

Ace Lamps, Unit 30 New Forest Enterprise Centre, Chapel Lane  
Totton, Southampton, Hampshire, SO40 9LA

Tel:023 80866728

Fax: 023 80667833

[www.deslamps.co.uk](http://www.deslamps.co.uk)